



Bullhead Safety® HEARING PROTECTION

Corded Reusable Silicone Earplugs

DESCRIPTION

These triple-flange silicone earplugs provide effective protection against hearing damage by greatly reducing environmental noise. High-visibility yellow and shaped to gently conform to the ear canal, the extra soft silicone is rated for a protection level of NRR 23 dB.

INDUSTRY

| | |
|---------------|--------------------------|
| Airport Crews | Utility/Waste Management |
| Construction | Transportation |
| Automotive | |
| Printing | |




FEATURES

- Cord helps prevent loss
- Environmentally friendly, 100% silicone
- Manufactured through vulcanization, not mold injected for ultimate flexibility
- Packaged 1 pair per personal carrying case (includes belt attachment)
- Extra-soft, lightweight silicone seals the ear canal without pressure
- Triple-flange shape with firm handle provides an easy to insert, snug fit while gently conforming to the ear canal

ITEM **HP-S2**

NRR **23 dB**



SPECIFICATIONS

| MATERIAL | SHAPE | COLOR | CORDED | METAL DETECTABLE | ANSI S3.19-1974 NRR RATING | EN 352-2: 2002 SNR RATING |
|----------|---------------|-----------|--------|------------------|----------------------------|---------------------------|
| SILICONE | TRIPLE-FLANGE | HV YELLOW | YES | NO | 23 dB | 28 dB |

ANSI S3.19-1974 SOUND ATTENUATION DATA:

| FREQUENCY (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 | NRR |
|-------------------------|------|------|------|------|------|------|------|------|------|-------|
| MEAN ATTENUATION (dB) | 28.7 | 25.9 | 31.3 | 27.3 | 35.1 | 39.4 | 40.3 | 46.2 | 46.2 | 23 dB |
| STANDARD DEVIATION (dB) | 5.5 | 4.5 | 4.5 | 2.8 | 4.3 | 4.2 | 5.6 | 6.1 | 3.7 | |

EN 352-2: 2002 SOUND ATTENUATION DATA:

| FREQUENCY (Hz) | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|-------------------------|-------------|-----------|-----------|-----------|------|------|------|
| SOUND ATTENUATION (dB) | 29.6 | 28.3 | 30.1 | 28.8 | 34.6 | 38.9 | 44 |
| STANDARD DEVIATION (dB) | 5.6 | 6 | 7.8 | 6 | 3.9 | 5.6 | 5.6 |
| ASSUMED PROTECTION (dB) | 24 | 22.3 | 22.3 | 22.8 | 30.7 | 33.3 | 38.4 |
| | SNR = 28 dB | H = 30 dB | M = 24 dB | L = 23 dB | | | |

PACKAGING

| | QUANTITY | ITEM ID |
|-------------------------|----------------|----------------|
| EACH PAIR | 1 | 810292029616 |
| INNER BOX | 100 PAIRS/PACK | 10810292029613 |
| CASE | 10 PK/CASE | 20810292029610 |
| CASE WEIGHT (IN POUNDS) | | 31.5 |

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
sales@BullheadSafety.com

BullheadSafety.com

