



**PYRAMEX**  
Perform At Your Peak

## Highlander Plus™

ANSI CE CSA BALLISTIC



FOAM  
PADDING



INCLUDES  
STRAP



VENTED  
FRAME

Indirect vented foam carriage

Detachable strap

Passes MIL-PRF 32432 High Velocity  
Impact Standards

Part No.	Black Frame
SBG5010DT ●●●	AF Clear H2X
SBG5020DT ●●●	AF Gray H2X
SBG5030DT ●●●	AF Amber H2X
SBG5055DT ●●●	AF Sky Red Mirror
SBG5080DT ●●●	AF I/O Mirror



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●), or Ballistic (MIL-PRF-32432) (●) standards. For specific lens options visit our website or contact your sales representative.

## Highlander Plus™

### General Specifications

Weight: 36 gm  
 PD: 68 mm  
 Bridge: 9 mm  
 Lens base: 8 curve  
 Lens size diagonal: 68.4 mm  
 Lens size vertical: 49 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 166 mm  
 Overall width (hinge - hinge): 136.5 mm  
 Closest point between temple tips: 80 mm  
 Closest point between lens: 15.6 mm

### Materials

Lens: polycarbonate  
 Frame: nylon  
 Foam: chloroprene rubber (CR)  
 Temples: polycarbonate  
 Hinge: polycarbonate & nylon  
 Screw: stainless steel  
 Strap: polyester  
 Strap holder: polyethylene (POM)  
 Nosepiece: polyvinyl chloride (PVC)

Part No.	Lens Markings	Frame Markings
SBG5010DT	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG5020DT	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG5030DT	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG5055DT	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG5080DT	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special purpose  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L1.7: 55% max visible light  
 L2.5: 29% max visible light

### Frame Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

