



PYRAMEX
Perform At Your Peak™

carhartt

Ironsides® ANSI



RUBBER
NOSEPIECE



RUBBER
TIPS



Straight-back vented, flexible temples

Rubber nosepiece

Rubber temple tips

Available in a Carhartt capture clam or polybag

Capture Clam Part No. **Black and Tan Frame**

| | | |
|--------------|----|------------------|
| CHB618DTCC • | AF | Sandstone Bronze |
| CHB620DTCC • | AF | Gray |
| CHB690DTCC • | AF | Antique Mirror |

Capture Clam Part No. **Realtree Xtra® Camo Frame**

| | | |
|---------------|----|------------------|
| CHRT618DTCC • | AF | Sandstone Bronze |
| CHRT620DTCC • | AF | Gray |
| CHRT690DTCC • | AF | Antique Mirror |

Polybag Part No. **Black and Tan Frame**

| | | |
|------------|----|------------------|
| CHB618DT • | AF | Sandstone Bronze |
| CHB620DT • | AF | Gray |
| CHB690DT • | AF | Antique Mirror |

Polybag Part No. **Realtree Xtra® Camo Frame**

| | | |
|-------------|----|------------------|
| CHRT618DT • | AF | Sandstone Bronze |
| CHRT620DT • | AF | Gray |
| CHRT690DT • | AF | Antique Mirror |



Polybags



Capture Clam



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ [•] standards. All lenses provide 99% protection from harmful UV rays and are hard coated polycarbonate scratch-resistant unless otherwise noted.



PYRAMEX
Perform At Your Peak™



carhartt

Ironside®

General Specifications

Weight: 30.6 gm
 Bridge: 13 mm
 Lens base: 8 curve
 Lens size diagonal: 64 mm
 Lens size vertical: 38 mm
 Lens thickness: 2.0 mm
 Overall length (lens - tip): 130 mm
 Overall width (hinge - hinge): 134 + 1 mm
 Closest point between temple tips: 98 + 5 mm
 Closest point between lens: 15 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temple: polycarbonate
 Temple tips: thermoplastic rubbers (TPR)
 Screw: stainless steel
 Nosepiece: thermoplastic rubbers (TPR)

Part No. Frame Marking

| | |
|-------------|-----------|
| CHB618DT | P Z87 + S |
| CHB618DTCC | P Z87 + S |
| CHB620DT | P Z87 + S |
| CHB620DTCC | P Z87 + S |
| CHB690DT | P Z87 + S |
| CHB690DTCC | P Z87 + S |
| CHRT618DT | P Z87 + S |
| CHRT618DTCC | P Z87 + S |
| CHRT620DT | P Z87 + S |
| CHRT620DTCC | P Z87 + S |
| CHRT690DT | P Z87 + S |
| CHRT690DTCC | P Z87 + S |

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967