

Legacy® ANSI • CE • UKCA • CSA •

Integrated side shields provide additional protection
// Lightweight spectacle – 23 gm // Custom
imprinting available

Lens and Temples | 8 Variations

- S10910S Clear
- S10910STM Clear **H2MAX AF**
- S10920S Gray
- S10920STM Gray **H2MAX AF**
- S10925S Light Gray
- S10925STM Light Gray **H2MAX AF**
- S10950SF 5.0 IR Filter
- S10960SF 3.0 IR Filter



Part No.	Lens Marking	Temple Marking	Measurements	Materials
S10910S	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 23 gm	Lens: polycarbonate
S10910STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3	PD: 64 mm	Nosepiece: polycarbonate
S10920S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Bridge: 10.7 mm	Side Shield: polycarbonate
S10920STM	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3	Lens base: 6 curve	Temples: polycarbonate
S10925S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	Lens size diagonal: 51.5 mm	Screw: stainless steel
S10925STM	P Z87 + U6 L1.7 X	P Z87 + / P c SEI Z94.3	Lens size vertical: 46 mm	
S10950SF	P Z87 + W5	P Z87 + / P c SEI Z94.3	Lens thickness: 2 mm	
S10960SF	P Z87 + W6	P Z87 + / P c SEI Z94.3	Overall length (lens - tip): 155 mm	
			Overall width (hinge - hinge): 136 mm	
			Closest point between temple tips: 98.3 mm	
			Closest point between lens: 20.3 mm	

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
W: Welding filter
X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
c SEI Z94.3: CAN/CSA standard for eye and face protection devices