

PM80 SERIES

ANSI/ASA S3.19-1974 | CE/UKCA EN 352:2020

NRR 25dB | SNR 27dB

Low-profile ear cup design // Height adjustment to fit most //
Fold-away padded headband // Custom imprinting available

- PM8010 Gray
- PM8031 Hi-Vis Lime
- PM8041 Hi-Vis Orange

Earmuff Breakdown

Headband: Polyoxymethylene (POM)
Headband Adjustment: Nylon + Glass-filled Polymer
Headband Cushion: Fabric with Foam Pad
Ear Cup and Volume Ring: Acrylonitrile Butadiene Styrene
Ear Cushion: Polyurethane (PU) Foam + Polyvinyl Chloride (PVC)
Foam Insert: Sponge Foam

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

Packaging

Box: 1 unit
Case: 36 units
Made in Taiwan



NRR ATTENUATION									
FREQUENCY (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
MEANS	14.9	20.9	32.0	39.3	38.0	35.1	35.9	38.4	36.4
STANDARD DEVIATION (dB)	2.2	2.4	3.5	3.0	2.7	3.0	3.6	3.5	2.5

NRR - 25dB

SNR ATTENUATION								
FREQUENCY (Hz)	63	123	250	500	1000	2000	4000	8000
MEAN ATTENUATION (dB)	15.1	14.4	18.2	26.1	33.6	31.4	32.8	33.3
STANDARD DEVIATION (dB)	3.2	3.6	5.3	2.8	3.2	3.3	3.7	3.7
APV (dB)	11.9	10.8	12.9	23.3	30.4	28.1	29.1	29.6

SNR - 27dB H - 29dB M - 25dB L - 17dB