



PYRAMEX
Perform At Your Peak

PMXSLIM® ANSI CE AUS



ADJUSTABLE
NOSEPIECE



CO-INJECTED
TEMPLES

Slim fit for smaller facial features

Soft, adjustable nosepiece

Co-injected temple design includes soft rubber tips for a non-slip fit

Part No.	Black Temples
SB7110S ●●	Clear
SB7110ST ●●●	AF Clear H2X
SB7120S ●●	Gray
SB7120ST ●●●	AF Gray H2X
SB7138S ●●●	Sandstone Bronze
SB7180S ●●●	I/O Mirror



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] (●) or Australian [AS/NZS 1337] (●) standards. For specific lens options visit our website or contact your sales representative.



PMXSLIM®

General Specifications

Weight: 25 gm
 PD: 68 mm
 Bridge: 14.5 mm
 Lens base: 10 curve
 Lens size diagonal: 137.7 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 170 mm
 Overall width (hinge - hinge): 129 mm
 Closest point between temple tips: 86 mm
 Closest point between lens: 9 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Side shields: polycarbonate
 Nosepiece: polyvinyl chloride (PVC)

Part No.	Lens Markings	Frame Markings
SB7110S	P Z87 + U6	P Z87 +
SB7110ST	P Z87 + U6	P Z87 +
SB7120S	P Z87 + U6 L2.5	P Z87 +
SB7120ST	P Z87 + U6 L2.5	P Z87 +
SB7138S	P Z87 + S	P Z87 +
SB7180S	P Z87 + U6 L1.7	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967