

Polyurethane Coated Vend-Packed Gloves with Cut, Abrasion, and Puncture Resistance

DESCRIPTION

This seamless glove features a 13-gauge HPPE brand fiber shell. The shell is enhanced by a polyurethane-dipped palm. Each pair of gloves is packaged for vending machines.



INDUSTRY

Automotive Assembly	Glass Handling
Metal Work	Small Parts Assembly
Construction	Metal Fabrication
Steel Framing	

FEATURES

- 13-gauge HPPE fiber shell offers great dexterity
- Polyurethane dip provides superior grip and comfort
- Overcast color on hem for easy size identification
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use
- ANSI/ISEA 105 Cut Level A2
- ASTM F2992-15 Results = 571 grams
- ANSI/ISEA 105 Abrasion Level 6
- ANSI/ISEA 105 Puncture Level 3
- ANSI/ISEA 105 Puncture Results: 92 Newtons
- EN 388 Levels: 3242X



SPECIFICATIONS

SHELL	GAUGE	SHELL COLOR	COATING	COATING COLOR	FINISH	CUFF
HPPE	13-Gauge	Salt-and-Pepper	Polyurethane	Gray	Smooth	Knit Wrist
ANSI CUT	ASTM F2992-15 RESULTS	ANSI ABRASION	ANSI PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS	
Level A2	571 Grams	Level 6	Level 3	92 Newtons	3242X	

PACKAGING

	QUANTITY	6(XS)	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	816368024752	816368024769	816368024776	816368024783	816368024790	816368024806
INNER PACK GTIN	12/PACK	10816368024759	10816368024766	10816368024773	20816368024787	10816368024797	10816368024803
CASE GTIN	6 PK/CASE	20816368024756	20816368024763	20816368024770	10816368024780	20816368024794	20816368024800
CASE WEIGHT (IN POUNDS)		8	8	9	10	11	13
OVERCAST COLOR		Purple	Red	Green	Brown	Black	Light Blue

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com


Global Glove
& Safety Manufacturing, Inc.