



RP3001 Reusable Corded Earplugs

NRR 25dB // SNR 30dB

Three flexible rubber flanges form a secure seal

Reusable earplugs can be cleaned with soap and water

PART NO.

RP3001 ● ●

RP3001PC ●

PYRP3001* ●

*Pyramex retail packaged product

STANDARDS

Meets ANSI S3.19-1974 and

CE EN-352:2002

GENERAL SPECIFICATIONS

Reusable: Yes

Metal Detectable: No

Plug Material: TP Rubber

Plug Color: Hi-vis orange

Plug Dimension: 1.5 x 2.8 cm

Cord Material: Nylon Cloth

Cord Color: Hi-vis lime

Cord Length: 70cm

SIZE

One size fits most

PACKAGING

RP3001 - Sold Individually | 50 per box | 20 boxes per case

PYRP3001 - Sold Individually | 12 per box | 18 boxes per case

PRODUCT GUIDELINES

The level of noise entering a person's ear, when hearing protection is worn as directed is approximated by the difference between the A-weighted environmental level and the NRR.

Example: 1. The environmental noise level at the ear is 92 dB(A).

2. The NRR is 32 decibels (dB).

3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in continuous noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.

**There's more to see at
PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967



PYRP3001

i All hearing protection meets ANSI S3.19 standards (●). Some options meet European (CE EN-352:2002) (●) standards. For more information visit our website or contact your sales representative.