

RENDEZVOUS®

Fully Adjustable Spectacles



Black Frame

Part	Lens
SB2810S●●●	<input type="checkbox"/> Clear
SB2810ST●●●●	<input type="checkbox"/> Clear H2X Anti-Fog
SB2815S●●●	<input type="checkbox"/> Coffee
SB2820S●●●	<input type="checkbox"/> Gray
SB2820ST●●●●	<input type="checkbox"/> Gray H2X Anti-Fog
SB2830S●●●	<input type="checkbox"/> Amber
SB2840S●●●	<input type="checkbox"/> Orange
SB2860S●●●	<input type="checkbox"/> Infinity Blue
SB2860ST●●●●	<input type="checkbox"/> Infinity Blue H2X Anti-Fog
SB2870S●●●	<input type="checkbox"/> Silver Mirror
SB2875S●●●	<input type="checkbox"/> Blue Mirror
SB2880S●●●	<input type="checkbox"/> Indoor/Outdoor Mirror

Crystal Clear Frame

Part	Lens
SCC2810S●●●	<input type="checkbox"/> Clear
SCC2810ST●●●●	<input type="checkbox"/> Clear H2X Anti-Fog
SCC2870S●●●	<input type="checkbox"/> Silver Mirror

Crystal Gray Frame

Part	Lens
SCG2810ST●●●●	<input type="checkbox"/> Clear H2X Anti-Fog

Crystal Blue Frame

Part	Lens
SCB2810S●●●	<input type="checkbox"/> Clear

- Temples adjust to four different lengths.
- Adjustable nose pad conforms to broad range of bridge sizes.
- Crafted from high grade polycarbonate, machined from virgin materials and formed to shape.
- Align lens angle to proper position for work application with ratcheting lens pitch adjustment.
- 9.5 base curve lens provides excellent side protection against wind and airborne particles, provides 99.9% protection against harmful UV rays.
- Passes MIL-PRF 32432 High Velocity Impact Standards.

GENERAL SPECIFICATION

Bridge: 9.6mm
Lens Base: 9.5 Curve
Lens Size Diagonal: 83mm
Lens Size Vertical: 45.5mm
Lens Thickness: 2.42mm
Overall Length (Lens-Tip): 54-166mm
Overall Width (Hinge-Hinge): 138mm
PD: 68mm
Weight: 28gm
Closest point between lens: 16.6mm
Closest point between temples tip: 75-76mm

PACKAGING

Polybag: 1pc


















Inner Box: 12 pcs

Case: 300 pcs

RENDEZVOUS®

Fully Adjustable Spectacles

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Contemporary design with dual-focus construction to fit contours of face
Frame	Polycarbonate	Lightweight & durable ventilation reduces chance of fogging
Side Shield	Polycarbonate	Integral to lens, provides excellent coverage
Nose Bridge	Polycarbonate	Break-through design, fully adjustable, soft touch & support, no pressure and slippage
Soft Nose Pad	PVC	
Sleeve (on temple)	Polycarbonate	Unique ratchet mechanism with length adjustable temple to create a custom fit. Slim design makes entire glass stylish & attractive
Temple		
Hinge	Polycarbonate	3 barrel type, integral to frame/ part (sleeve)
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB2810S	 Clear	P Z87 + U6	P Z87 +
SB2810ST	 Clear H2X Anti-Fog	P Z87 + U6	P Z87 +
SB2815S	 Coffee	P Z87 + U6 L3	P Z87 +
SB2820S	 Gray	P Z87 + U6 L2.5	P Z87 +
SB2820ST	 Gray H2X Anti-Fog	P Z87 + U6 L2.5	P Z87 +
SB2830S	 Amber	P Z87 + U6	P Z87 +
SB2840S	 Orange	P Z87 + S	P Z87 +
SB2860S	 Infinity Blue	P Z87 + U6 L1.3	P Z87 +
SB2860ST	 Infinity Blue H2X Anti-Fog	P Z87 + U6 L1.3	P Z87 +
SB2870S	 Silver Mirror	P Z87 + S	P Z87 +
SB2875S	 Blue Mirror	P Z87 + S	P Z87 +
SB2880S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +
SCB2810S	 Clear	P Z87 + U6	P Z87 +
SCC2810S	 Clear	P Z87 + U6	P Z87 +
SCC2810ST	 Clear H2X Anti-Fog	P Z87 + U6	P Z87 +
SCC2870S	 Silver Mirror	P Z87 + S	P Z87 +
SCG2810ST	 Clear H2X Anti-Fog	P Z87 + U6	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact