



Ridgeline Bump Caps NON-RATED

Polyethylene material // For applications where hard hats are not required, but some protection from minor bumps and scalp lacerations are needed // Available with 4-point glide lock suspension // Ventilation holes // Replaceable sweat band // Not designed to meet the safety standards for industrial head protection // Custom imprinting available

4-Point Glide Lock | 9 Variations

HP40010	White
HP40011	Black
HP40012	Gray
HP40015	Brown
HP40020	Red
HP40030	Yellow
HP40035	Green
HP40040	Orange
HP40060	Blue



Materials

Shell: high density polyethylene (HDPE)

Suspension: high density polyethylene (HDPE)

Sweat band: polyester fabric & polyurethane (PU) foam

General Specifications

Weight: 215 gm

Shell thickness: 1.35-2.15mm

Dimensions: 27.5cm x 19.5cm x 14cm

Suspension adjust sizing: 6.5 - 8

Suspensions: 4-point glide lock suspension

Standards: Non-rated

Markings

Date code: indicated month and year when the shell was molded -

does not indicate service life



Product Guidelines

Maximum service life of 5 years (shell) $\&\,1\,\mbox{year}$ (suspension) from the time of first use

Never alter or modify the shell or suspension system

Inspect the hard hat each time before use and replace if there is ANY sign of damage

Replace hard hat after it receives a considerable impact

Accessories such as liners have not been tested to the requirement of this standard

Clean only with mild soap and lukewarm water

Store hard hat in a clean, dry place that is out of direct sunlight $% \left(1\right) =\left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left($

Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage