

RIDGELINE® FULL BRIM

SIGNATURE STYLE, PROVEN PROTECTION

Experience top-notch protection with the Ridgeline® Full Brim hard hat. Its durable ABS shell provides superior impact resistance and lightweight comfort, while the full brim design ensures maximum coverage from environmental hazards. The innovative adjustable, swinging ratchet suspension allows the hard hat to sit lower on the head for a more comfortable fit. The ratchet suspension offers effortless adjustment, fitting sizes 6.5 to 8 securely.



DURABLE
ABS SHELL



ACCESSORY
COMPATIBLE



COMFORTABLE
PADDING



VENTED
OPTIONS



RATCHET
SUSPENSION



ABS SHELL

VENTED
(FOR SELECT MODELS)

ACCESSORY SLOTS
(ALL VENTED AND
SELECT NON-VENTED
MODELS)

FULL COVERAGE

SWINGING RATCHET
SUSPENSION

HP54110V

i Temporary mixed inventory may occur due to supply chain conditions. Product features may vary slightly. All inventory conforms to applicable ANSI standards.

FEATURES

Robust, Lightweight Shell: ABS shell ensures durable, lightweight protection

Complete Cover: Full brim design ensures maximum protection from environmental hazards while enhancing comfort and visibility

Accessory Compatibility (All Vented and Select Non-Vented Models): Universal accessory slots to add additional protection

Effortless Adjustment: 4 or 6-point swinging ratchet suspension easily adjusts to provide a perfect fit across all head sizes

Enhanced Ventilation (For Select Models): Strategically placed vents improve airflow and reduce heat buildup, providing cooler wear during extended use

Hygienic Solution: Replaceable sweatband promotes cleanliness and comfort

Engineered Toughness: Meets ANSI/ISEA Z89.1-2014 Type I,  certified for CAN/CSA Z94.1-2015 Type I to ensure durability and confidence in performance



LEARN MORE
ABOUT THE RIDGELINE
FULL BRIM KEY FEATURES

PYRAMEX®       

P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM

RIDGELINE® FULL BRIM

SIGNATURE STYLE, PROVEN PROTECTION



DURABLE
ABS SHELL



ACCESSORY
COMPATIBLE



COMFORTABLE
PADDING



VENTED
OPTIONS



RATCHET
SUSPENSION

VARIATIONS

NON-VENTED

4-Point Ratchet Suspension | 20 Variations

HP 54110	White
HP 54111	Black
HP 54112	Gray
HP 54113	Slate Gray
HP 54116	Matte White Graphite Pattern
HP 54116S	Shiny White Graphite Pattern
HP 54117	Matte Black Graphite Pattern
HP 54117S	Shiny Black Graphite Pattern
HP 54118	Matte Copper Graphite Pattern
HP 54120	Red
HP 54121	Matte Red Graphite Pattern
HP 54122	Matte Blue Graphite Pattern
HP 54123	Matte Silver Graphite Pattern
HP 54124	Matte Lime Graphite Pattern
HP 54130	Yellow
HP 54131	Hi-Vis Lime
HP 54135	Green
HP 54141	Hi-Vis Orange
HP 54160	Blue
HP 54170	Pink

6-Point Ratchet Suspension | 5 Variations

HP 56110	White
HP 56120	Red
HP 56130	Yellow
HP 56135	Green
HP 56160	Blue

VENTED

4-Point Ratchet Suspension | 9 Variations

HP 54110V	White
HP 54111V	Black
HP 54113V	Slate Gray
HP 54117V	Matte Black Graphite Pattern
HP 54130V	Yellow
HP 54131V	Hi-Vis Lime
HP 54135V	Green
HP 54141V	Hi-Vis Orange
HP 54160V	Blue



HP6PTSUS – Transforms 4-point suspensions to 6-point for cap style and full brim hard hats



REPLACEMENT PARTS



HPRBANDR – Ridgeline cap style and full brim hard hat sweat suspension



HPR541 – 4-point ratchet suspension

i Temporary mixed inventory may occur due to supply chain conditions. Product features may vary slightly. All inventory conforms to applicable ANSI standards.

MATERIALS

Shell: ABS (Acrylonitrile Butadiene Styrene) Plastic
Sweatband: Polyester + Polyurethane (PU) Foam
Suspension: HDPE (Polypropylene) + High Impact Nylon

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov

MARKINGS

Standard: ANSI/ISEA Z89.1-2014 + CAN/CSA Z94.1-2015
Type: Type I Full Brim Hard Hat
Class: Non-Vented – Class E (Electrical) Rated for 20,000 Volts, Vented – Class C (Conductive) Does Not Offer Electrical Protection – Class G (General) Rated for 2,200 Volts
LT: Low Temperatures Protection up to -22°F HT: High Temperatures Protection up to 140°F
HV: Meets All Requirements for High-Visibility (HP54131, HP54141, HP54131V, HP54141V)
Date Code: Indicates Month and Year Shell was Molded - Does Not Indicate Service Life.

Product markings may vary // Updated as of 06.26

GENERAL SPECIFICATIONS

Weight: 378 gm
Shell Thickness: 1.7-4 mm
Dimensions: 31 x 27 x 15.2 cm
Suspension Adjust Sizing: 6.5 to 8
Suspension: Adjustable with Ratcheting Wheel

PRODUCT GUIDELINES

Never alter or modify the shell or suspension system. Always use original replacement parts. Decals/stickers are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage.

Inspect your hard hat shell and suspension on a regular basis. Check for cracks or faulty parts each time it is to be used. If you notice any sign of damage, the faulty part should be discarded and immediately replaced. Inspect the hard hat each time before use and replace immediately if there is any sign of damage.

The service life of a hard hat begins when the hard hat is put into service. Maximum service life is 5 years for the shell and 1 year for the suspension, beginning immediately upon first use. If the hard hat has received a considerable strike, it should be replaced immediately, even if there is no visible damage. Only use genuine Pyramex accessories and replacement parts that have been approved for use with this helmet.

Clean only with mild soap and lukewarm water. DO NOT USE paints, chemicals, gasoline, or similar substances on the hard hat. If these substances are applied on the shell, its impact resistance and other features could be decreased and could be dangerous for the user.

Store hard hat in a cool place out of direct sunlight. Do not store in vehicles where the interior temperature can become extreme and cause deterioration of the hard hat.

PYRAMEX®

P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM