



**PYRAMEX**  
Perform At Your Peak™

**carhartt** 

**Rockwood®** **ANSI** **CSA**



ADJUSTABLE  
NOSEPIECE



CO-INJECTED  
TEMPLES

Suspended anti-fog lens

Adjustable rubber nosepiece and co-injected temple tips

Available in a Carhartt capture clam or polybag

Capture Clam Part No.	Black and Tan Frame	
CHB718DTCC ●●	AF	Sandstone Bronze
CHB720DTCC ●●	AF	Gray
Polybag Part No.	Black and Tan Frame	
CHB710DT ●●	AF	Clear
CHB718DT ●●	AF	Sandstone Bronze
CHB720DT ●●	AF	Gray



Polybags



Capture Clam

There's more to see at  
**PYRAMEXSAFETY.COM**  
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ (●) and Canadian (CSA Z94.3) (◉) standards. All lenses provide 99% protection from harmful UV rays and are hard coated polycarbonate scratch-resistant unless otherwise noted.

## Rockwood®

### General Specifications

Weight: 24.6 gm  
 Bridge: 18 mm  
 Lens base: 8 curve  
 Lens size diagonal: 78 mm  
 Lens size vertical: 45 mm  
 Lens thickness: 2.0 mm  
 Overall length (lens - tip): 130 mm  
 Overall width (hinge - hinge): 132 + 1 mm  
 Closest point between temple tips: 80 + 5 mm  
 Closest point between lens: 20 mm

### Materials

Lens: polycarbonate  
 Frame: polycarbonate  
 Temple: polycarbonate  
 Temple tips: thermoplastic rubbers (TPR)  
 Screw: stainless steel  
 Nosepiece: thermoplastic rubbers (TPR) and wire

### Part No.

### Lens Marking

### Temple Marking

Part No.	Lens Marking	Temple Marking
CHB710DT	P	P Z87 + / P c SEI CAN/CSA Z94.3-15
CHB718DT	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15
CHB718DTCC	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15
CHB720DT	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15
CHB720DTCC	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special purpose  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

