

SL T2™ FRONT BRIM

ENGINEERED PROTECTION THAT SURROUNDS

Elevate the SL T2 Safety Helmet with the SL T2 Front Brim, crafted for extended sun and rain protection. This innovative brim swiftly clips into the helmet, providing additional coverage without compromising upward visibility.



FEATURES

Extended Protection: Extends helmet brim for enhanced sun and rain protection, ensuring comfort and focus

Upward Visibility: Made of tinted see-through material, the brim shields without compromising upward visibility, promoting clarity and safety

Effortless Attachment: Attach and detach the brim with ease, thanks to its intuitive design that ensures a snug and secure fit every time

 HPT2BRIM sold separately from the SL T2 Safety Helmet.



TOOLS AT YOUR FINGERTIPS

Learn more about the SL T2 Helmet and Accessories

SL T2™ FRONT BRIM

ENGINEERED PROTECTION THAT SURROUNDS

Elevate the SL T2 Safety Helmet with the SL T2 Front Brim, crafted for extended sun and rain protection. This innovative brim swiftly clips into the helmet, providing additional coverage without compromising upward visibility.

VARIATION

HPT2BRIM



MATERIALS

Brim: PC (Polycarbonate)

Grips: TPE (Thermoplastic Elastomer)

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov

GENERAL SPECIFICATIONS

Weight: 40g

Overall Length: 195mm

Overall Width: 126mm

Overall Height: 32.5mm

Updated as of 06.24

INSTRUCTIONS

To Attach Front Brim to Helmet

1. Turn the helmet upside down, ensuring the brim is also upside down.
2. Align the slots on the brim with the two slots on the inside front of the helmet.
3. Push firmly to click them into place, ensuring a secure attachment.

To Remove Front Brim from Helmet

1. Firmly grasp grips at edge of brim.
2. Pull out and down to detach the brim from the helmet.