SL T2™ SAFETY HELMET









COMFORTABLE PADDING



ENGINEERED PROTECTION THAT SURROUNDS

Experience unparalleled protection with the SLT2 Safety Helmet. Featuring advanced EPS foam that absorbs impacts from all angles, coupled with a lightweight ABS shell. The helmet is compatible with SLTZ accessories for customized safety solutions. All-day comfort is ensured with strategically placed padding and effortless ratchet suspension adjustment. The 4-point cross-over chin strap secures the helmet for confident performance. Available in vented and non-vented options.



FEATURES

Advanced Impact Absorption: EPS foam liner absorbs forces from all angles for unparalleled protection

Robust, Lightweight Shell: ABS shell ensures durable, lightweight protection

Accessory Compatibility: Pair with SL T2 accessories for tailored safety solutions

Comfortable Padding: Designed with strategically placed soft padding to ensure all-day comfort

Effortless Adjustment: Ratchet suspension easily adjusts to provide a perfect fit across all head sizes

Secure-Fit Design: 4-point cross-over chin strap with quick-release buckle for a secure, comfortable fit

Engineered Toughness: Meets ANSI/ISEA Z89.1-2014 (R2019) Type II standard to ensure durability and confidence in performance



SL T2 HELMET AND ACCESSORIES

SL T2™ SAFETY HELMET







COMFORTABLE PADDING

ENGINEERED PROTECTION THAT SURROUNDS

Experience unparalleled protection with the SLT2 Safety Helmet. Featuring advanced EPS foam that absorbs impacts from all angles, coupled with a lightweight ABS shell. The helmet is compatible with SLT2 accessories for customized safety solutions. All-day comfort is ensured with strategically placed padding and effortless ratchet suspension adjustment. The 4-point cross-over chin strap secures the helmet for confident performance. Available in vented and non-vented options.

VARIATIONS

VENTED

Ratchet Suspension | 5 Variations

HPT261110V	White
HPT261111V	Black
HPT261162V	Light Blu
HPT261130V	Yellow
HPT261140V	Orange



NON-VENTED

Ratchet Suspension | 5 Variations

HPT261110	White
HPT261111	Black
HPT261162	Light Blu
HPT261130	Yellow
HPT261140	Orange



MATERIALS

Shell: ABS (Acrylonitrile Butadiene Styrene) Plastic

Inner Lining: Dual Density EPS (Expanded Polystyrene) Foam

Sweatband: Fleece + Foam

Chin Strap: Nylon + Silicone + PS (Polystyrene) + PP (Polypropylene)

Buckle: POM (Polyoxymethylene)

Suspension: PP (Polypropylene)

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

GENERAL SPECIFICATIONS

Weight: 510g	
Shell Thickness: 2.5mm	
Dimensions: 10.25" x 8.5" x 7"	
Suspension Adjust Sizing: 65/8 to 77/8	
Suspension: Adjustable with Ratcheting Wheel	
Chin Strap: 4-Point Cross-Over Adjustable	

MARKINGS

Standard: ANSI/ISEA Z89.1-2014 (R2019)

Type: Type II Safety Helmet

Class: Non-Vented - Class E (Electrical) Rated for 20,000 Volts, Vented – Class C (Conductive) Does Not Offer Electrical Protection

LT: Low Temperatures Protection up to -22°F HT: High Temperatures Protection up to 140°F

Date Code: Indicates month and year shell was molded - does not indicate service life.

Product markings may vary // Updated as of 06.24

PRODUCT GUIDELINES

Maximum shelf life of 5 years (shell) from the time of first use - whichever occurs first.

Never alter or modify the shell, suspension, or chin strap.

Inspect the hard hat each time before use and replace immediately if there is any sign of damage.

Replace the helmet after it receives a considerable impact.

Only use genuine Pyramex accessories and replacement parts that have been approved for use with this helmet.

Clean only with mild soap and lukewarm water.

Store helmet in a clean, dry place that is out of direct sunlight.

Do not use paints, chemicals, adhesives, gasoline, or similar substances on the helmet.

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage.