



Sitecore™ ANSI CE CSA



Built-in rubber nosepiece

Flexible and ventilated temples

Ratcheting temples

Temples adjust to three different lengths

Part No.	Black and Gray Frame
SBG10110D ●●	Clear
SBG10110DTM ●●	AF Clear H2MAX
SBG10120D ●●	Gray
SBG10120DTM ●●	AF Gray H2MAX
SBG10130D ●●	Amber
SBG10180D ●●	I/O Mirror

Part No.	Gray and Lime Frame
SGL10110D ●●●	Clear
SGL10110DTM ●●●	AF Clear H2MAX
SGL10120D ●●●	Gray
SGL10120DTM ●●●	AF Gray H2MAX
SGL10180D ●●●	I/O Mirror



vimeo.com/pyramex/h2max



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provides 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European EN166 (●), Canadian CSA Z94.3 (●) – SEI third-party certification.

Sitecore™

General Specifications

Weight: 24.4 gm
 Bridge: 10.6 mm
 Lens base: 8 curve
 Lens size diagonal: 74 mm
 Lens size vertical: 41.5 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 158 mm
 Overall width (hinge - hinge): 132.5 mm
 Closest point between temple tips: 55 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Nosepiece: thermoplastic rubber (TPR)
 Ratchet: polycarbonate
 Sleeve: nylon
 Temple: nylon
 Screw: stainless steel

Part No.	Lens Marking	Temple Marking
SBG10110D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10110DTM	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10120D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10120DTM	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10130D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10180D	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10110D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10110DTM	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10120D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10120DTM	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10180D	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% max visible light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967