



MCR
SAFETY

24 Goggles Series Specification Sheet

PRODUCT DESCRIPTION:

The body design of the 24 Series provides a wide, unobstructed field of vision and can be worn with most half-mask respirators. The transparent protective PVC body permits a comfortable fit over prescription eyewear. The optional soft foam lining cushions the face and improves the seal. Offered in both scratch-resistant polycarbonate lens and anti-fog lens, the 24 Series is also available with either a wide elastic headband or a neoprene headband. Meets or exceeds ANSI Z87+ and CSA Z94.3.



FEATURES:

- Impact Resistant
- Fits over Prescription Glasses
- Optional Foam Lining
- Indirect Ventilation
- ANSI Z87+ and CSA Z94.3

TECHNICAL DATA FOR: 2410F

Series	24	ANSI Z87+	Yes
Category	Goggles	CAN/CSA Z94.3	Yes
Goggle Type	Indirect Vented	ANSI D4 DUST	Yes
Dielectric	Yes	Packaging	White Inner Box
Anti-Fog	Yes		
Scratch Resistant	Yes		
Frame Material	PVC		
Case Pack	60 pair	Case Weight	24.600 lb.
Case Dimensions	21.654 x 17.323 x 21.654	Made In	Mexico, Taiwan

Item No:	Lens Options:	Lens Coating:	Scratch Resistant:	VLT %:	Frame Color:	Goggle Type:
2400	Clear	Duramass Hard Coat	Yes	90	Smoke	Indirect Vented
2400F	Clear	Duramass Hard Coat	Yes	90	Smoke	Indirect Vented

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved



MCR
SAFETY

24

Goggles

Series

Specification Sheet

Item No:	Lens Options:	Lens Coating:	Scratch Resistant:	VLT%:	Frame Color:	Goggle Type:
2410	Clear	Duramass Anti-Fog	Yes	90	Smoke	Indirect Vented
2410B	Clear	Duramass Anti-Fog	Yes	90	Smoke	Indirect Vented
2410F	Clear	Duramass Anti-Fog	Yes	90	Smoke	Indirect Vented
2410NF	Clear	Duramass Anti-Fog	Yes	90	Smoke	Indirect Vented

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved