



MCR
SAFETY

BearKat (BK3)

Safety Glasses

Value Series

Specification Sheet

PRODUCT DESCRIPTION:

The BearKat® BK3 features a soft, secure gel nosepiece for additional comfort. It's super well thought-out construction combines the best in safety, comfort, and affordability! Your vision is unobstructed by the one-piece wraparound lens, which by its tight fit allows you maximum safety. Comfort is enhanced by the flexible temples and the non-slip temple sleeves, which are notched for a clip-on breakaway cord!



FEATURES:

- Soft, secure gel nosepiece
- Single lens design with integral side shields for unobstructed view
- Non-Slip soft temple material
- Exclusive Duramass® scratch resistant coating
- Rugged polycarbonate lens filters 99.9% of harmful U.V. rays

TECHNICAL DATA FOR: BK312AF

Series	BearKat (BK3)	ANSI Z87+	Yes
Category	Safety Glasses		
Anti-Fog	Yes		
Scratch Resistant	Yes		
Packaging	White Inner Box		
Case Pack	144 pair	Case Weight	14.139 lb.
Case Dimensions	21.850 x 14.370 x 13.189	Made In	Taiwan

Item No:	Lens Options:	Lens Coating:	Scratch Resistant:	VLT%:	Frame Color:	Temple Color:	Temple Sleeve:
BK310	Clear	Duramass Hard Coat	Yes	90	N/A	Clear	Black
BK310AF	Clear	Duramass Anti-Fog	Yes	90	N/A	Clear	Black
BK312	Gray	Duramass Hard Coat	Yes	13	N/A	Gray	Black



MCR
SAFETY

BearKat (BK3)

Safety Glasses

Value Series

Specification Sheet

Item No:	Lens Options:	Lens Coating:	Scratch Resistant:	VLT%:	Frame Color:	Temple Color:	Temple Sleeve:
BK312AF	Gray	Duramass Anti-Fog	Yes	13	N/A	Gray	Black
BK313	Light Blue	Duramass Hard Coat	Yes	68	N/A	Light Blue	Black
BK314	Amber	Duramass Hard Coat	Yes	80	N/A	Amber	Black
BK317	Silver Mirror	Duramass Hard Coat	Yes	13	N/A	Smoke	Black
BK318	Blue Mirror	Duramass Hard Coat	Yes	13	N/A	Smoke	Black
BK319	I/O Clear Mirror	Duramass Hard Coat	Yes	36	N/A	Clear	Black

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved