



**MCR
SAFETY**

HIT FR Gear

Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The H1 Henley Shirt features a 100% FR Cotton material for Maximum Comfort. The Max Comfort™ material meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Gray, Navy and Tan

FEATURES:

- Max Comfort™ Fabric NFPA 2112 UL Certified
- All Trims are NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection Standard
- NFPA 70E HAZARD, HRC 2
- ATPV ASTM 1959 9.6 cal/cm², HRC 2
- Henley is UL & NFPA 2112 CERTIFIED
- **Max Comfort™ 7.0 oz. 100% Cotton FR interlock knit shell**
- 3 button placket front
- Left chest pocket
- Fabric is moisture wicking and breathable
- Rib knit collar and cuff
- Hi-temperature FR poly buttons



APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking, Mining

TECHNICAL DATA FOR: H1T

Series	Max Comfort	Front Closure	Button
Category	FR Gear	NFPA 2112 Cert.	Yes
Size	Large	NFPA 70E Cert.	Yes
Material	Flame Resistant, 100% Cotton	ASTM 1930 Cert.	Yes

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved



MCR
SAFETY

HIT
FR Gear
Specification Sheet

Material Weight	- Max Comfort	ASTM F1506 Cert.	Yes
Flame Resistant	7.0 oz.	Hazard Risk Category	HRC2
	Flame Resistant		

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
H1TS	34-36	N/A	N/A	N/A	N/A	N/A	29.520
H1TM	38-40	N/A	N/A	N/A	N/A	N/A	30.636
H1TL	42-44	N/A	N/A	N/A	N/A	N/A	32.364
H1TXL	46-48	N/A	N/A	N/A	N/A	N/A	34.128
H1TX2	50-52	N/A	N/A	N/A	N/A	N/A	385.920
H1TX3	54-56	N/A	N/A	N/A	N/A	N/A	38.052
H1TX4	58-60	N/A	N/A	N/A	N/A	N/A	40.968
H1TX5	62-64	N/A	N/A	N/A	N/A	N/A	42.444