

PGX I Goggles Series Specification Sheet

PRODUCT DESCRIPTION:

Consumers committed to sourcing premium products take confidence with PGX1® goggles. Four (4) styles feature design elements that include polycarbonate lens and body with thermal plastic rubber (TPR) seal,multiple points of indirect venting,external liquid diversion channel, and internal perspiration channel. Two adjustable strap options are available including elastic or TPR as well as two lens offerings in clear or gray. Additional feature include anti-fog coating.



FEATURES:

- Polycarbonate body and lens with thermo plastic rubber (TPR) seal
- External liquid diversion channels
- Multiple points of indirect venting for increased airflow
- Available with Elastic or TPR adjustable strap

TECHNICAL DATA FOR: PGX110AF

Series PGX1 **ANSI Z87+** Yes AS/NZS 1337.1 Yes Category Goggles Goggle Type Indirect Vented **CE EN166** Yes **ANSI D3 SPLASH Dielectric** Yes Yes Anti-Fog Yes **ANSI D4 DUST** Yes **Scratch Resistant** Yes **ANSI D5 FINE DUST** Yes

Frame Material Polycarbonate Packaging White Inner Box

Case Pack 60 pair Case Weight 22.560 lb.

Case Dimensions 19.291 x 18.110 x 18.307 Made In Sri Lanka, Taiwan

Item No:	Lens Options:	Lens Coating:	Scratch Resistant:	VLT %:	Frame Color:	Goggle Type:
PGX110AF	Clear	Duramass Anti-Fo	og Yes	90	Silver	Indirect Vented
PGX112AF	Gray	Duramass Anti-Fo	og Yes	13	Silver	Indirect Vented
PGX120AF	Clear	Duramass Anti-Fog Yes		90	Silver	Indirect Vented
PGX122AF	Gray	Duramass Anti-Fo	og Yes	13	Silver	Indirect Vented

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com



PGX I
Goggles
Series
Specification Sheet