

carbartt <u></u>

Spokane® (ANSI) CSA



Flexible rubber nosepiece

Co-injected straight-back temples

Unique half-frame design for the active lifestyle

Available in a Carhartt capture clam or polybag

Capture Clam Part No.	Blac	k Frame
CHB310DCC • •		Clear
CHB318DCC ••		Sandstone Bronze
CHB320DCC • •		Gray
Polybag Part No.	Blac	k Frame
CHB310D ● ●		Clear
CHB318D • •		Sandstone Bronze
CHB320D ● ●		Gray









Polybags





All safety eyewear meets ANSI Z87.1+ (\bullet) and Canadian (CSA Z94.3) (\bullet) standards. All lenses provide 99% protection from harmful UV rays and are hard coated polycarbonate scratch-resistant unless otherwise noted.



Spokane®

General Specifications

Weight: 24 gm Bridge: 15mm Lens base: 8 curve Lens size diagonal: 78 mm Lens size vertical: 42 mm Lens thickness: 2.0 mm Overall length (lens - tip): 125 mm Overall width (hinge - hinge): 137 + 1 mm Closest point between temple tips: 107 + 5 mm Closest point between lens: 17 mm

Materials

Lens: polycarbonate Frame: polycarbonate Temple tips: thermoplastic rubbers (TPR) Screw: stainless steel Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking	
CHB310D	Р	P Z87 + / P c SEI CAN/CSA Z94.3-15	
CHB310DCC	Р	P Z87 + / P c SEI CAN/CSA Z94.3-15	
CHB318D	P + S	P Z87 + S / P c SEI CAN/CSA Z94.3-15	
CHB318DCC	P + S	P Z87 + S / P c SEI CAN/CSA Z94.3-15	
CHB320D	P + S	P Z87 + S / P c SEI CAN/CSA Z94.3-15	
CHB320DCC	P + S	P Z87 + S / P c SEI CAN/CSA Z94.3-15	

Lens Marking Symbols

P: Manufacturer's mark

S: Special purpose

Temple Marking Symbols

P: Manufacturer's mark Z87: ANSI standard for eye and face protection devices +: High impact S: Special purpose c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at **PYRAMEXSAFETY.COM** (P) 800.736.8673 | (F) 901.861.4967

