

TRIFECTA®



Part **Lens**
SB76WMD Punched Steel

- Wrap-around punched steel lens does not fog up or become scratched.
- Provides excellent eye protection for work environments with high humidity and flying particles.

GENERAL SPECIFICATION
Bridge: 12mm
Lens Base: 8 curve
Closest point between temple tips: 86mm
Closest point between lens: 15mm
Lens Size Diagonal: 60.5mm
Lens Size Vertical: 44.5mm
Lens Thickness: 0.6mm
Overall Length [Lens-Tip]: 162mm
Overall Width [Hinge-Hinge]: 140mm
PD: 68mm
Weight: 36gm

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Stainless Steel	8 base wrap around mesh lens
Frame Insert	Nylon	Mesh lens insert frame, interchangeable
Frame	Polycarbonate	Clipped with mesh frame insert
Nose Piece	Polycarbonate	Integral to frame, universal
Temple	Polycarbonate	Straight side type
Temple Tip	PVC	Slipped on temple, spatula type
Screw	Stainless Steel	Standard hinge screw
Hinge	Polycarbonate	3 barrel type