

VG80 Series

ANSI/ASA S3.19-1974

NRR 37dB when worn with earplugs

Low-profile ear cup design // Height adjustment to fit all sizes // Fold-away, padded headband // Packaged in a VG clamshell with free disposable earplugs// Available in a freestanding/hanging VG clamshell // Custom imprinting available

VGPM8010C Gray

VGPM8010PC Pink

VGPM8011C Black

VGPM8031C Hi-Vis Lime

VGPM8041C Hi-Vis Orange

VGPM8063C Teal

VGPM8065C Purple





Imprint Program

Imprint your logo or your customer's logo on Pyramex eye protection, ear muffs, hard hats and hi-vis apparel. In order to start the process, we only need your artwork. Vectored artwork is preferred, but if unavailable, we can work from any files you provide. There may be an additional charge for re-drawing artwork to a vectored format. Contact your sales representative for further details.

Product Guidelines

The level of noise entering a person's ear, when hearing protection is worn as directed is closely approximated by the difference between the A-weighted environmental level and the NRR.

Example: 1. The environmental noise level at the ear is 92 dB(A).

2. The NRR is 26 decibels (dB).

3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.

All hearing protection meets ANSI/ASA S3.19-1974 standards. For more information visit our website or contact your sales representative.